

Boston Chemcat (UHMW)

Applications:

- Transfer of acids, chemicals, solvents, and petroleum
- Loading or unloading pumping, suction, or gravity flow
- Resistant to chemical, petroleum, solvent, and ozone
- Won't contaminate or discolor fluids

Tube:

- Ultra High Molecular Weight Polyethylene UHMW

Reinforcement:

- Textile, 2 ply, or 4 ply and helical wire

Cover:

- Purple EPDM

Temp Range:

- -45°F to +160°F



Part #	I.D. (in.)	O.D. (in.)	Working PSI	Bend Radius (in.)	Weight (lbs/ft)	Standard Length
CCAT075	3/4	1.20	200	4.0	.31	150
CCAT100	1	1.53	200	5.5	.55	150
CCAT125	1 1/4	1.88	200	6.0	.67	150
CCAT150	1 1/2	2.13	200	7.5	.89	150
CCAT200	2	2.63	200	8.0	1.16	150
CCAT250	2 1/2	3.13	200	8.0	1.42	150
CCAT300	3	3.63	200	9.0	1.68	150
CCAT400	4	4.67	150	15.0	2.26	150
CCAT600	6	7.00	150	30.0	7.21	150

OHS Corrugated UHMW Hose

Applications:

- Transfer of acids, chemicals, solvents, and petroleum
- Loading or unloading, pumping, suction, or gravity flow
- Resists abrasion, chemicals, and petroleum
- FDA approved material; will not contaminate or discolor fluids

Tube:

- Ultra high molecular weight polyethylene (U.H.M.W.)

Reinforcement:

- Textile, 2 ply and helical wires

Cover:

- Green Corrugated EPDM

Temp Range:

- -45°F to +220°F



Part #	I.D. (in.)	O.D. (in.)	Working PSI	Bend Radius (in.)	Weight (lbs/ft)	Standard Length
OHSUH150	1 1/2	2.13	200	4.0	.89	150
OHSUH200	2	2.63	200	5.0	1.16	150
OHSUH300	3	3.63	200	6.5	1.68	150
OHSUH400	4	4.68	150	9.5	2.26	150

Goodyear FabChem

Applications:

- This hose handles the majority of common industrial chemicals in pressure, gravity flow and suction services.

Tube:

- Pliosyn UHMW

Reinforcement:

- Spiral-plied synthetic fabric with double wire helix

Cover:

- Green Versigard synthetic rubber with bright orange longitudinal stripe, corrugated (wrapped impression)

Temp Range:

- -40°F to +150°F



Part #	I.D. (in.)	O.D. (in.)	Working PSI	Bend Radius (in.)	Weight (lbs/ft)	Standard Length
GFC100	1	1.53	200	5.0	.72	150
GFC125	1 1/4	1.88	200	8.0	.86	100
GFC150	1 1/2	2.13	200	8.0	.89	150
GFC200	2	2.63	200	9.0	1.13	150
GFC300	3	3.63	150	16.0	1.64	150
GFC400	4	4.69	150	21.0	2.39	100