

## Stainless Steel Blower Hose R360S Unlined [packed]

### Applications:

- For engine intake and exhaust systems, conduit, granular materials, spouts, casings, and chimney liners

### Tube:

- Smooth bore interlocked stainless steel .018" strip thickness

### Temp Range:

- -60°F to +400°F



Part #	I.D. (in.)	O.D. (in.)	Working PSI	Bend Radius (in.)	Weight (lbs/ft)	Standard Length
R360S150	1 1/2	-	15	7.3	.94	25,50,60
R360S175	1 3/4	-	15	9.2	1.10	25,50,60
R360S200	2	-	15	10.5	1.23	25,50,60
R360S225	2 1/4	-	15	10.8	1.40	25,50,60
R360S250	2 1/2	-	15	12.0	1.53	25,50,60
R360S275	2 3/4	-	15	12.8	1.67	25,50,60
R360S300	3	-	15	14.0	1.82	25,50,60
R360S350	3 1/2	-	15	15.5	2.11	25,50,60
R360S400	4	-	15	16.5	2.40	25,50,60
R360S450	4 1/2	-	15	18.0	2.70	25,50,60
R360S500	5	-	15	20.0	2.99	25,50,60
R360S600	6	-	15	26.0	3.57	25,50,60

## Hot Air Blower Hose - Rubber

### Applications:

- Hot air blower hose, hot, dry, non-oily air applications
- Resists aging, heat (intermittent service to 350°F), and weather

### Tube:

- EPDM

### Temp Range:

- -95°F to +300°F



Part #	I.D. (in.)	O.D. (in.)	Working PSI	Bend Radius (in.)	Weight (lbs/ft)	Standard Length
WHA300	3	3.73	150	9.0	2.3	100
WHA400	4	4.61	100	11.0	2.9	100