

General Service Air/Water

Applications:

- Air and water applications requiring maximum flexibility
- Outstanding resistance to heat and ozone
- Limited oil resistance

Tube:

- EPDM Black

Reinforcement:

- Synthetic, high tensile textile cord

Cover:

- Red EPDM

Temp Range:

- +25°F to +150°F

For air
and water
without oil
mist.



Part #	I.D. (in.)	O.D. (in.)	Bend Radius (in.)	Working PSI	Weight (lbs/ft)	Standard Length
150 PSI						
AFR125P150	1 1/4	1.73	10	150	.59	300
AFR150P150	1 1/2	1.98	12	150	.70	250
AFR200P150	2	-	-	150	-	-
200 PSI						
AFR025P200	1/4	.47	3	200	.08	650
AFR032P200	5/16	-	-	200	-	650
AFR038P200	3/8	.66	3	200	.14	650
AFR050P200	1/2	.81	5	200	.20	650
AFR058P200	5/8	.93	6	200	.23	650
AFR075P200	3/4	1.08	6	200	.29	650
AFR100P200	1	1.39	8	200	.45	400
AFR125P200	1 1/4	-	-	200	-	-
AFR150P200	1 1/2	-	-	200	-	-
250 PSI						
AFR025P250	1/4	.47	3	250	.08	650
AFR038P250	3/8	.66	3	250	.14	650
AFR050P250	1/2	.81	5	250	.20	650
AFR058P250	5/8	.93	6	250	.23	650
AFR075P250	3/4	1.13	6	250	.34	650
300 PSI						
AFR025P300	1/4	.63	-	300	.14	650
AFR038P300	3/8	.69	-	300	.18	650
AFR050P300	1/2	.75	-	300	.23	650
AFR075P300	3/4	1.19	-	300	.40	650
AFR100P300	1	-	-	300	-	-