

Goodyear Hi-Per

Application:

- A premium hose which is FEP (Fluorinated Ethylene-Propylene) lined to handle a broad spectrum of fluids and materials in a wide variety of applications

Tube:

- FEP has FDA/USDA compliant materials

Cover:

- Blue Versigard synthetic rubber with bright orange spiral transfer tape

Reinforcement:

- Spiral-plied synthetic fabric with double wire helix

Temp Range:

- -40°F to +300°F



Part #	I.D. (in.)	O.D. (in.)	Working PSI	Bend Radius (in.)	Weight (lbs/ft)	Standard Length
GHIPER-050	1/2	0.97	200	3.0	0.7	100
GHIPER-075	3/4	1.11	200	5.0	0.56	100
GHIPER-100	1	1.52	200	8.0	0.71	100
GHIPER-125	1 1/4	1.73	200	11.0	0.84	100
GHIPER-150	1 1/2	2.13	200	14.0	1.24	100
GHIPER-200	2	2.69	200	18.0	1.71	100
GHIPER-250	2 1/2	3.14	200	22.0	2.01	60
GHIPER-300	3	3.67	200	35.0	2.52	60

PeraFlex GGP Hydro Carbon Hose

Applications:

- Transfer of hydrocarbon products; petroleum, diesel, kerosenes, fuel oils, solvents
- Rated for 100% aromatic content
- Resists abrasion, ozone, and fire w/ a 5 to 1 safety ratio

Tube:

- Seamless polypropylene tubes and film barriers

Reinforcement:

- Internal wire: galvanized External wire: galvanized

Cover:

- Black vinyl coated polyester

Temp Range:

- -40°F to +212°F



Part #	I.D. (in.)	O.D. (in.)	Working PSI	Bend Radius (in.)	Weight (lbs/ft)	Standard Length
GGP100	1	-	200	2.0	.65	80
GGP125	1 1/4	-	200	-	-	80
GGP150	1 1/2	-	200	3.0	1.0	80
GGP200	2	-	200	3.5	1.2	80
GGP250	2 1/2	-	200	4.0	2.0	80
GGP300	3	-	200	5.5	2.4	80
GGP400	4	-	200	6.5	3.5	80
GGP600	6	-	200	22.0	7.4	50
GGP800	8	-	200	29.0	12.5	50