

Steam Hose

Applications:

- Transfer of steam for processing products and cleaning equipment
- Transfer of steam or hot 200°F detergent-type solutions for cleaning of equipment, tanks, buildings, etc.
- Resists heat, aging, ozone, and weather
- Meets RMA standards; 10 to 1 safety factor

Tube:

- EPDM

Reinforcement:


- Wire, 2 braid

Cover:

- Red pin pricked EPDM, black

Temp Range:

- +450°F



Part #	I.D. (in.)	O.D. (in.)	Working PSI	Bend Radius (in.)	Weight (lbs/ft)	Standard Length (ft)
CONR050	1/2	1.03	250	-	.46	50
CONR075	3/4	1.34	250	-	.70	50
CONR100	1	1.56	250	-	.96	50

Chlorobutyl Steam Hose

Applications:

- Transfer of steam for processing products and cleaning equipment
- Transfer of steam or hot 200°F detergent-type solutions for cleaning of equipment, tanks, buildings, etc.
- Resists heat, aging, ozone, and weather
- Meets RMA standards; 10 to 1 safety factor

Tube:

- Patrex(Chlorobutyl)

Reinforcement:


- Wire, 2 braid, sepaplate static wire

Cover:

- Black and red stripe pin pricked EPDM

Temp Range:

- +450°F



Part #	I.D. (in.)	O.D. (in.)	Working PSI	Bend Radius (in.)	Weight (lbs/ft)	Standard Length (ft)
CONSTD050	1/2	1.13	250	-	.55	50
CONSTD075	3/4	1.38	250	-	.78	50
CONSTD100	1	1.63	250	-	1.00	50
CONSTD125	1 1/4	1.94	250	-	1.35	50
CONSTD150	1 1/2	2.19	250	-	1.55	50
CONSTD200	2	2.69	250	-	1.94	50

White Washdown Hose

Applications:

- For general clean-up and hot water wash down service in dairies, creameries, meat packing houses, food processing and bottling
- Resists abrasion, heat, mold, and fungus
- Suitable for hot water 200°F

Tube:

- White synthetic rubber

Reinforcement:


- 2 layers of synthetic yarns

Cover:

- White synthetic rubber cover

Temp Range:

- -40°F to +200°F



Part #	I.D. (in.)	O.D. (in.)	Working PSI	Bend Radius (in.)	Weight (lbs/ft)	Standard Length (ft)
WWD050	1/2	0.91	250	-	.31	700
WWD075	3/4	1.25	200	-	.54	700