

KanaFlex 220RS Water Suction\Discharge & Sewer Hose

Applications:

- Heavy duty liquid suction hose for use in construction dewatering, liquid waste, cesspool cleaning, septic handling, agricultural applications, and marine use

Tube:

- Smooth bore black SBR rubber polyethylene

Reinforcement:

- Rigid PVC helix

Cover:

- Smooth black SBR rubber polyethylene

Temp Range:

- -40°F to +140°F



Part #	I.D. (in.)	O.D. (in.)	Vacuum 72°F, in. Hg	Working PSI	Bend Radius (in.)	Weight (lbs/ft)	Standard Length (ft)
220RS150	1 1/2	1.85	29.8	50	3.0	.50	100
220RS200	2	2.40	29.8	50	4.0	.74	100
220RS250	2 1/2	2.99	29.8	50	5.0	1.01	100
220RS300	3	3.50	29.8	43	6.0	1.30	100
220RS400	4	4.57	29.8	38	9.0	2.01	100
220RS600	6	6.69	28.0	23	15.0	3.37	100

KanaFlex 300EPDM Water Suction & Discharge Hose

Applications:

- Heavy duty liquid suction hose for use in construction dewatering, liquid waste, cesspool cleaning, septic handling, agricultural applications and marine use

Tube:

- Smooth bore black EPDM rubber

Reinforcement/Cover:

- Corrugated green polyethylene helix

Temp Range:

- -40°F to +140°F



Part #	I.D. (in.)	O.D. (in.)	Vacuum 72°F, in. Hg	Working PSI	Bend Radius (in.)	Weight (lbs/ft)	Standard Length (ft)
300EPDM100	1	1.34	29.8	50	1.9	.23	100
300EPDM125	1 1/4	1.65	29.8	50	3.2	.34	100
300EPDM150	1 1/2	1.84	29.8	50	3.2	.40	100
300EPDM200	2	2.43	29.8	50	5.2	.67	100
300EPDM250	2 1/2	2.99	29.8	50	5.6	.92	100
300EPDM300	3	3.52	29.8	43	7.1	1.10	100
300EPDM400	4	4.61	29.8	38	11.0	1.84	100
300EPDM600	6	6.81	28.0	23	20.0	3.07	100